



### **Things to Be Noted During Fueling**

- Ø When fueling, prevent fuel from spilling out, especially when fueling a motor vehicle. Never let fuel spill on a high temperature engine or exhaust pipe.
- Ø If some fuel spills out, wipe it up immediately. Rags with fuel stains should be kept properly in a lidded container.
- Ø When a passenger bus comes to the station for fueling, there shall be no passengers on the bus.
- Ø Never fill gasoline or kerosene, etc. into an insulative container, such as a plastic bucket or basin.
- Ø When using the nozzle, do not carry out an incorrect operation such as hitting a fuel receiving container or pressing a switch with the nozzle; such an operation may damage the nozzle or cause fuel leakage.
- Ø Before you lift the nozzle for testing, you must make sure that the nozzle is in an shut-off condition, to prevent the occurrence of fuel spilling after the nozzle is lifted. When testing, you can turn on the nozzle for fueling only after the nozzle reliably touches the wall of the metal bucket.
- Ø If someone is smoking or using a cell phone inside the station, you should stop fueling immediately.
- Ø If there is/are high intensity lightning or frequent thunderbolts in the sky above the gas station, you should stop fueling operations, and take protective measures.
- Ø During fueling, you should pay close attention to the oil tank opening, to prevent fuel from spilling out.
- Ø After fueling, you should pull out the nozzle immediately, to prevent it from being dragged away.
- Ø Before and after fueling, you should keep the rubber hose on the fueling island, to prevent it from being run over by vehicles.
- Ø When fueling and payment procedures are completed, you should, in a timely manner, guide the vehicle to leave the gas station.